

#12012 #12013 #12014

M8N GPS



Descriptions:

The M8N GPS has an UBLOX M8N module, IST8310 compass, tri-colored LED indicator, and a safety switch. There are 3 different connectors options for different purposes.

This module ships with a baud rate of 38400 5Hz

Features and Specifications:


- Ublox Neo-M8N module
- Industry leading -167 dBm navigation sensitivity
- Cold starts: 26s
- LNA MAX2659ELT+
- 25 x 25 x 4 mm ceramic patch antenna
- Rechargeable Farah capacitance
- Low noise 3.3V regulator
- Current consumption: less than 150mA @ 5V
- Fix indicator LEDs
- Protective case
- 26cm cable included
- Diameter 50mm total size, 32 grams with case.

Pin Map

Type your text

Holybro M8N GPS (JST GHR1.25mm 10 pin cable):


This JST GH 10Pin connector can be use d on Pixhawk Series 10pin"GPS Module" or "GPS1" input port.



Holybro M8N GPS for Pix32


(Molex1.25mm 6pin & 4pin &3pin cable):

These Molex1.25mm 6pin & 4pin & 3pin connectors are for Pix32 "Switch", "GPS", and "I2C" input ports.




Holybro M8N 2nd GPS(JST GHR1.25m m 6pin cable):

This JST GH 6Pin connector can be used on Pixhawk Series 6pin "UART & I2C" or "GPS2" input port as secondary GPS.





Dimensions



DIMENSIONS IN MILLIMETERS

Package Included:

M8N GPS Module *1

'X' type folding pedestal mount *1

Carbon rod 100mm *1

Holybro is a registered trademark of Holybro, registered in the U.S. and other countries. ©Copyright 2018 Holybro. All Rights Reserved.

