



31.9	19.5	24.8	12.4	3*5
25.7	19.5	18.6	12.4	3*4
19.5	19.5	12.4	12.4	3*3
19.5	13.3	12.4	6.2	2*3
13.3	13.3	6.2	6.2	2*2
25.7	7.1	18.6	/	1*4
19.5	7.1	12.4	/	1*3
13.3	7.1	6.2	/	1*2
C	B	A2	A1	PIN

Specifications:

Rated Current	9~15A AC,DC (AWG #16)				角度	±3°	设计		日期	
Rated Voltage	300V AC,DC				63 < L	±0.3°	审核		日期	
Contact Resistance	0.02MΩ max				16 < L ≤ 63	±0.2°	核准		日期	
Insulation Resistance	1000MΩ min				4 < L ≤ 16	±0.1°	比例	1:1	视图	
Withstanding Voltage	1500V AC/minute				1 < L ≤ 4	±0.05°	单位	MM	页码	1/1
Temperature Range	-25 C to +85 C	胶壳	PA66	白	L ≤ 1	±0.05°	编号			
Applicable wire Range	AWG #22 to #16	部件	材质	颜色	未详细说明之公差		版本	BY/2020		

温州柏雨电子有限公司

名称	L6.2 公壳
型号	L6.2-YA