

Magnet Mount Antennas

2G / 3G / 4G Applications



LAMBDOID
WIRELESS

Technical Specification		Photograph / Drawing
Model Number	LWC-4G-MM-06 (3.0M RG58)	
Frequency (MHz)	698 – 960 MHz & 1710 – 2690 MHz	
Gain	7/ 8 dBi	
Impedance (Ω)	50	
VSWR	< 2.5	
Polarization	Linear	
Power Handling (W)	50	
HPBW	H: 360°; V: 30° / 40°	
Cable Type/ Length	RG58, 3.0m	
Connector	SMA-Plug	
Mechanical Specification		Salient Features
Dimension (mm)	320 x φ45	<ul style="list-style-type: none"> - Compact Size - Low Cost - Connector of your choice - Any cable length - Powerful magnet.
Housing	Spring Steel Powder Coated	
Weight	< 140g	
Environmental Specification		Applications
Operational Temperature	-30° to 60° C	<ul style="list-style-type: none"> - GSM - 3G - 4G - ISM/ WiFi/ Zigbee/ BLE
Humidity	5 – 75%	

LAMBDOID WIRELESS COMMUNICATIONS

Address: 647/2, 11th Main, 5th Block, Jayanagar, Bengaluru 560 041. INDIA.

Tel: +91 80 2659 5337; **Email:** info@lambdoid.net; **Website:** www.lambdoid.net